

Mil spec #	Insulation	Voltage	Temp	Conductor	Awg Range
Mil-W-22759/1	PTFE Glass	600	200 C	SPC	22 THRU 4/0
Mil-W-22759/2	PTFE Glass	600	260 C	NPC	22 THRU 4/0
Mil-W-22759/3	TFE Glass	600	260 C	NPC	22 THRU 2/0
Mil-W-22759/4	TFE	600	200 C	SPC	22 THRU 2/0
Mil-W-22759/5	PTFE Mineral Filled	600	200 C	SPC	24 THRU 4
Mil-W-22759/6	PTFE Mineral Filled	600	260 C	NPC	24 THRU 4
Mil-W-22759/7	PTFE Mineral Filled	600	200 C	SPC	24 THRU 4
Mil-W-22759/8	PTFE Mineral Filled	600	260 C	NPC	24 THRU 4
Mil-W-22759/9	PTFE	1000	200 C	SPC	28 THRU 8
Mil-W-22759/10	PTFE	1000	260 C	NPC	28 THRU 8
Mil-W-22759/11	PTFE	600	200 C	SPC	28 THRU 8
Mil-W-22759/12	PTFE	600	260 C	NPC	28 THRU 8
Mil-W-22759/13	FEP	600	135 C	TPC	24 THRU 1/0
Mil-W-22759/14	FEP	600	135 C	TPC	26 THRU 12
Mil-W-22759/15	FEP	600	135 C	SP ALLOY	26 THRU 20
Mil-W-22759/16	ETFE	600	150 C	TPC	20 THRU 2/0
Mil-W-22759/17	ETFE	600	150 C	SP ALLOY	20 THRU 20
Mil-W-22759/18	ETFE	600	150 C	TPC	26 THRU 10
Mil-W-22759/19	ETFE	600	150 C	SP ALLOY	26 THRU 20
Mil-W-22759/20	PTFE	1000	105 C	SP ALLOY	28 THRU 20
Mil-W-22759/21	PTFE	1000	260 C	NP ALLOY	28 THRU 20
Mil-W-22759/22	PTFE	600	200 C	SP ALLOY	28 THRU 20
Mil-W-22759/23	PTFE	600	260 C	NP ALLOY	28 THRU 20
Mil-W-22759/28	PTFE	600	260 C	SPC	28 THRU 8
Mil-W-22759/29	PTFE	600	260 C	NPC	28 THRU 8
Mil-W-22759/30	PTFE	600	200 C	SP ALLOY	28 THRU 20
Mil-W-22759/31	PTFE	600	260 C	NP ALLOY	28 THRU 20
Mil-W-22759/32	XL ETFE	600	150 C	TPC	30 THRU 12
Mil-W-22759/33	XL ETFE	600	200 C	SP ALLOY	30 THRU 20
Mil-W-22759/34	XL ETFE	600	150 C	TPC	24 THRU 2/0
Mil-W-22759/35	XL ETFE	600	200 C	SP ALLOY	26 THRU 20
Mil-W-22759/41	XL ETFE	600	200 C	NPC	26 THRU 2/0
Mil-W-22759/42	XL ETFE	600	200 C	NP ALLOY	26 THRU 20
Mil-W-22759/43	XL ETFE	600	200 C	SPC	26 THRU 2/0
Mil-W-22759/44	XL ETFE	600	200 C	SPC	28 THRU 12
Mil-W-22759/45	XL ETFE	600	200 C	NPC	28 THRU 12
Mil-W-22759/46	XL ETFE	600	200 C	NP ALLOY	28 THRU 20
Mil-W-22759/80	L/Weight Composite	600	150 C	TPC	26 THRU 10
Mil-W-22759/81	L/Weight Composite	600	200 C	SP ALLOY	26 THRU 20
Mil-W-22759/82	N/Weight Composite	600	260 C	NP ALLOY	26 THRU 20
Mil-W-22759/83	N/Weight Composite	600	200 C	SPC	8 THRU 4/0
Mil-W-22759/84	N/Weight Composite	600	260 C	NPC	8 THRU 4/0
Mil-W-22759/85	N/Weight Composite	600	150 C	TPC	8 THRU 4/0
Mil-W-22759/86	N/Weight Composite	600	200 C	SPC	26 THRU 4/0
Mil-W-22759/87	N/Weight Composite	600	260 C	NPC	26 THRU 4/0
Mil-W-22759/88	N/Weight Composite	600	150 C	TPC	26 THRU 4/0
Mil-W-22759/89	N/Weight Composite	600	200 C	SP ALLOY	26 THRU 20
Mil-W-22759/90	N/Weight Composite	600	260 C	NP ALLOY	26 THRU 20
Mil-W-22759/91	L/Weight Composite	600	200 C	SPC	26 THRU 10
Mil-W-22759/92	L/Weight Composite	600	260 C	NPC	26 THRU 10